



# Expanding Blade Agitator

Air Driven Expanding Blade Bung-Mounted Agitator



## Quick install, expanding blade mixer for sealed drums or tanks

- SST construction
- Standard 1-1/2 and 2 inch bung connections
- Adjustable blade design for positioning within the tank
- Simple screw in installation

PROVEN QUALITY. LEADING TECHNOLOGY.



## Target Applications

- Foam
- Polyurea
- General Finishing
- For any sealed container with 1-1/2 inch or 2 inch bung access

## Ordering Information

- 24C728 Low Viscosity, 1 HP  
 24C729 High Viscosity, 1.75 HP

## Technical Specifications

Maximum air input pressure .....	100 psi (7 bar, 0.7 MPa)
Maximum recommended agitator speed .....	500 rpm
Air consumption at 400 rpm with 100 psi (0.7 MPa, 7 bar) air inlet pressure	
Model 24C728 (low viscosity) .....	12 scfm (0.34 m <sup>3</sup> /min)
Model 24C729 (high viscosity) .....	22 scfm (0.62 m <sup>3</sup> /min)
Noise Level at 100 psi (0.7 MPa, 7 bar), maximum load*	
Model 24C728 (low viscosity)	
Pressure .....	72.32 dB
Power .....	80 dB
Model 24C729 (high viscosity)	
Pressure .....	75.74 dB
Power .....	82.32 dB
Wetted Parts .....	303, 18-8, and 304 stainless steel
Bung adapter thread sizes .....	1 1/2-11.5 npsm and 2-11.5 npsm
Weight	
Model 24C728 (low viscosity) .....	9.6 lb (4.4 kg)
Model 24C729 (high viscosity) .....	13.1 lb (5.9 kg)

*\*Tested in water to ISO 9614-2.*

**CONTACT US TODAY**

**info@ultimatelinings.ie or CALL: 086 8209150 / 086 822 7258**